Montana Board of Oil and Gas Conservation Environmental Assessment

Operator: Continental Resources, Inc.
Well Name/Number: Snow 1-13H
Location: NW NE Section 13 T23N R54 E
County: Richland, MT; Field (or Wildcat) W/C (Bakken Horizontal)
Air Quality
(possible concerns)
Long drilling time: No, 20 to 30 days drilling time.
Unusually deep drilling (high horsepower rig): No, triple derrick rig to drill a single lateral
horizontal Bakken Formation test, 19,864'MD/9,984'TVD.
Possible H2S gas production: Slight chance H2S gas from Mississippian Formations.
In/near Class I air quality area: No, Class I air quality area near to this location.
Air quality permit for flaring/venting (if productive): Yes, DEQ air quality permit required
under 75-2-211.
Mitigation: _X Air quality permit (AQB review)
All quality permit (AQB review) Gas plants/pipelines available for sour gas
Special equipment/procedures requirements
Other:
Comments: No special concerns – using triple rig to drill a single lateral
horizontal Bakken Formation test, 19,864'MD/9,984'TVD. If there is an existing
gathering system for natural gas in the area, then associated gas can be gathered or if
no gathering system nearby gas can be flared under Board Rule 36.22.1220.
Water Quality
Water Quality (possible concerns)
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based
(possible concerns) Salt/oil based mud: _Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001).
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location.
(possible concerns) Salt/oil based mud: _Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: _No high water table anticipated at this location. Surface drainage leads to live water: _Yes, nearest drainages are unnamed ephemeral
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location.
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface.
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface. Porous/permeable soils: No, silty sandy clay soils.
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface. Porous/permeable soils: No, silty sandy clay soils. Class I stream drainage: No Class I stream drainages in the area of review.
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface. Porous/permeable soils: No, silty sandy clay soils. Class I stream drainage: No Class I stream drainages in the area of review. Mitigation:
Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface. Porous/permeable soils: No, silty sandy clay soils. Class I stream drainage: No Class I stream drainages in the area of review.
(possible concerns) Salt/oil based mud: Yes to intermediate casing string hole to be drilled with oil based invert drilling fluids (oil/water ratio of 70/30 to 80/20). Horizontal lateral will be drilled with brine water. Surface casing hole will use freshwater and freshwater mud system (Rule 36.22.1001). High water table: No high water table anticipated at this location. Surface drainage leads to live water: Yes, nearest drainages are unnamed ephemeral tributary drainages to Fox Lake, about 1/2 of a mile to the east and about 3/4 of a mile to the southwest from this location. Water well contamination: None, closest water wells are about 5/8 of a mile to the south, about 3/4 of a mile to southeast, about 7/8 of a mile to the southeast and about 7/8 of a mile to the northwest from this location. Depth of these stock and domestic water wells range from 60' to 390'. Surface hole will be drilled with freshwater and freshwater mud system, Rule 36.22.1001. Surface casing will be set at 1780' and cemented to surface. Porous/permeable soils: No, silty sandy clay soils. Class I stream drainage: No Class I stream drainages in the area of review. Mitigation: Lined reserve pit

X Off-site disposal of solids/liquids (in approved facility)
X Other: Lined cuttings pit will be used since this is a closed loop mud system
to be employed.
Comments: 1780' of surface casing enough to cover the base of the Fox Hills
and cemented to surface adequate to protect freshwater zones, Rule 36.22.1001.
Soils/Vegetation/Land Use
Q
(possible concerns)
Steam crossings: No stream crossings anticipated.
High erosion potential: No high erosion potential at this location. The location will
require a moderate cut, up to 10.7' and small fill, up to 2.9', required.
Loss of soil productivity: No, location will be restored after drilling if unproductive. If
productive, unused portion of this drilling location will be restored.
Unusually large wellsite: No a large wellsite, 400'X450' location size required. Damage to improvements: Slight, surface use is a grazing land.
Conflict with existing land use/values: Slight
Mitigation
Avoid improvements (topographic tolerance)
Exception location requested
X Stockpile topsoil
Stream Crossing Permit (other agency review)
X Reclaim unused part of wellsite if productive
Special construction methods to enhance reclamation
Other
Comments: Access will be over existing county road #324 and existing lease
road. About 2504' of new access road will be built into this location off the existing lease
road. Cuttings will be buried in the lined cuttings pit. Oil based drilling fluids will be
recycled. Reserve pit fluids will be hauled to a commercial disposal. Pit will be allowed to dry and then plead by filling and mixing in with allow subspile. No appoint appears
to dry and then closed by filling and mixing in with clay subsoils. No special concerns.
Health Hazards/Noise
(possible concerns)
Proximity to public facilities/residences: Closest residences are about ¾ of a mile to the
southeast, about 1.25 miles to the southeast and about 1.5 miles to the northeast from
this location. The town of Lambert, Montana is about 7 miles to the southeast from this
<u>location.</u> Possibility of H2S: <u>Slight chance of H2S from Mississippian Formations.</u>
Size of rig/length of drilling time: Triple drilling rig/short, 20 to 30 days drilling time.
Mitigation:
X Proper BOP equipment
Topographic sound barriers
H2S contingency and/or evacuation plan
Special equipment/procedures requirements
Other:
Comments: Adequate surface casing cemented to surface with an operational
BOP stack (annular and double ram (pipe and blinds) rated for 5,000 psig)
should mitigate any problems, Rule 36.22.1014.

Wildlife/recreation

(possible concerns) Proximity to sensitive wildlife areas (DFWP identified): Fox Lake State Game Management Area is about 5.8 miles to the southeast from this location. Proximity to recreation sites: Fox Lake State Game Management Area is about 5.8 miles to the southeast from this location. Creation of new access to wildlife habitat: No Conflict with game range/refuge management: No Threatened or endangered Species: Species identified as threatened or endangered are the Pallid Sturgeon, Interior Least Tern, Whooping Crane and Piping Plover. Candidate specie is the Sprague's Pipit and the Greater Sage Grouse. NH tracker website indicate zero (0) species of concern in this township and range.
Mitigation: Avoidance (topographic tolerance/exception) Other agency review (DFWP, federal agencies BLM, DSL) Screening/fencing of pits, drillsite Other: Comments: Private grazing surface lands. There may be species of concern that maybe impacted by this wellsite. We ask the operator to consult with the surface owner as to what he would like done, if a species of concern are discovered at this location. No concerns.
Historical/Cultural/Paleontological (possible concerns) Proximity to known sites: None identified. Mitigation avoidance (topographic tolerance, location exception) other agency review (SHPO, DSL, federal agencies BLM)
Other: Comments: Private grazing surface lands. There may be possible historical/cultural/paleontological sites that maybe impacted by this wellsite. We ask the operator to consult with the surface owner as to his desires to preserve these sites or not, if they are found during construction of the wellsite.
Social/Economic (possible concerns) Substantial effect on tax base Create demand for new governmental services Population increase or relocation Comments: Wildcat well. No concerns

Remarks or Special Concerns for this site

<u>Continental will drill a single lateral Bakken Formation horizontal well test, 19,864'MD/9,984'TVD. No special concerns.</u>

Summary: Evaluation of Impacts and Cumulative effects

I conclude that the approval of the subject Notice of Intent to Drill (does/ <u>does not</u>) constitute a major action of state government significantly affecting the quality of the human environment, and (does/ <u>does not</u>) require the preparation of an environmental impact statement.
Prepared by (BOGC): /s/Steven Sasaki (title:) Chief Field Inspector Date: March 18, 2013
Other Persons Contacted:
Montana Bureau of Mines and Geology, GWIC website (Name and Agency) Water wells in Richland County (subject discussed) March 18, 2013
US Fish and Wildlife, Region 6 website (Name and Agency) ENDANGERED, THREATENED, PROPOSED AND CANDIDATE SPECIES MONTANA COUNTIES, Richland County (subject discussed)
March 18, 2013 (date)
Montana Natural Heritage Program Website (Name and Agency) Heritage State Rank= S1, S2, S3 T23N R54E (subject discussed)
March 18, 2013 (date)
Montana Cadastral Website (Name and Agency) Surface Ownership and surface use Section 13 T23N R54E (subject discussed)
March 18, 2013 (date)
If location was inspected before permit approval: Inspection date: Inspector: Others present during inspection: